



WITH SÜDMETALL

ÜCONTROL FAMILY



HANDHELD
TRANSMITTER



WLAN HUB



ÜSMART
RELAY



AUTO LOCKING
MODULE



FINGERPRINT
READER WITH
KEYPAD



SMART HOME
AUTOMATION
INTERFACE



KEYPAD



ÜLOCK BL



FACIAL RECOGNITION
READER WITH KEYPAD



ÜROUND



ÜCONTROL APP



WHAT IS ÜCONTROL ?

ÜControl is a **flexible smart home solution** that provides a **unified management platform** via the **free ÜControl app** for iOS and Android. It offers everything from a direct Bluetooth connection to the device through to Wi-Fi connectivity for devices anywhere in the world.

At the heart of the ÜControl system is the free ÜControl app (for Android and iOS). It allows users to **manage devices** and **user permissions** with ease. **Time-based permissions** can also be set up conveniently via the app, enabling features such as automatic locking at specific times or access authorization for a limited period.

The hardware behind this solution includes, among other things, the ÜTopic Smart Lock — a **retrofit motor for mechanical lock cylinders** that enables motorized locking and unlocking of the door.



The system can be operated via a **keypad**, a **fingerprint reader with integrated keypad**, a **remote control**, **ÜRound**, **facial recognition**, or simply with your **smartphone** using the free ÜControl app.

In addition to ÜTopic, the **ÜLock wireless security lock** and the **ÜSmart Relay** can also be operated via the ÜControl app and the control methods described above, and can be fully integrated into the system. In this sense, ÜControl can be said to open every door and gate for you.

The ÜControl system was specifically designed for retrofit applications. The ÜTopic smart lock from this product family can be used with any door featuring a cylinder lock, meaning the existing cylinder does not need to be replaced and can continue to be used. The ÜLock replaces your mechanical lock and engages the external lever handle once access has been successfully authorized. It also offers the highest security standards thanks to its mechanical forced locking mechanism.

Installing the various access devices does not require annoying or time-consuming drill holes, and the app makes setup incredibly easy. If you have a garage door or an existing door with an electric strike or motor lock, the ÜSmart Relay provides a simple retrofit solution that opens up every possibility.

With Südmittel, everything is under ÜCONTROL

WHY ÜCONTROL ?

The ÜControl system provides a unified management platform via the free ÜControl app for iOS and Android, offering everything from a direct Bluetooth connection to the device through to Wi-Fi connectivity for devices anywhere in the world. Benefit from a seamless, fully integrated system from a single source, regularly enhanced with new features, intelligent integrations and innovative products — and perfectly suited for retrofit applications.



i 32 app users
including up to 3 master users

ÜTOPIC SMARTLOCK RX

- Rechargeable via USB-C (battery life approx. 6 months, depending on usage)
- Quick installation with no key adjustment required
- Suitable for all Euro profile cylinders
- Can also be mounted using an adhesive pad if there is no cylinder protrusion
- Highly secure Bluetooth connection
- Extra-quiet operation thanks to an adjustable silent mode
- Locking and unlocking from the inside by simply turning the ÜTopic
- Adjustable motor speed via the app (also suitable for multi-point locking systems)
- Can be opened without latch retraction
- Can also be used with profile cylinders that are not lockable from both sides
- Acoustic warning when battery charge drops below 20%
- Dimensions: Ø 55 mm, height 60 mm

ART.-N°	€/PIECE
77.96.0017 (stainless steel look)	208,00



i 32 app users
including up to 3 master users

ÜTOPIC SMARTLOCK RX

- Rechargeable via USB-C (battery life approx. 6 months, depending on usage)
- Quick installation with no key adjustment required
- Suitable for all Euro profile cylinders
- Can also be mounted using an adhesive pad if there is no cylinder protrusion
- Highly secure Bluetooth connection
- Extra-quiet operation thanks to an adjustable silent mode
- Locking and unlocking from the inside by simply turning the ÜTopic
- Adjustable motor speed via the app (also suitable for multi-point locking systems)
- Can be opened without latch retraction
- Can also be used with profile cylinders that are not lockable from both sides
- Acoustic warning when battery charge drops below 20%
- Dimensions: Ø 55 mm, height 60 mm

ART.-N°	€/PIECE
77.96.0016 (black, matt finish)	250,00



ÜTOPIC SAMPLE STAND

- Sample stand in wood/anthracite look
- Includes high-quality stainless steel door fitting
- Includes security cylinder with 4 keys

ART.-N°	DESCRIPTION	€/PIECE
77.96.0080	Sample stand ÜTopic RX	415,00



ÜLOCK FULL-LEAF BL BATTERY Comfort or Premium

General product features of ÜLock-B and ÜLock-Z:

- › Self-locking function, whisper-quiet latch bolt 20 mm (stainless steel)
- › Electronics protected inside the lock case
- › Tamper-protected, with the programming button integrated into the battery compartment
- › Standard long-life batteries – service life approx. 1 year (AAA Energizer Ultimate Lithium / D standard & CH standard) (SAFT LS 14250 / AT standard)
- › Status display available in the app (locked / unlocked)
- › OTA updates directly via the app
- › Office mode (permanently unlocked), either one-time or recurring cycle (adjustable from-to)

Specifications of ÜLock-B:

- › External lever handle can be engaged electrically
- › Premium version incl. certifications:
EN 179 / EN 1125 / EN 1634-1 / EN 14846
- › Panic function

Specifications of ÜLock-Z:

- › Both lever handles can be engaged electrically
- › No panic function
- › Premium version incl. certifications:
EN 1634-1 / EN 14846

**Version Z
on request!**

ART.-N°	DESCRIPTION	€/PIECE
depending on the version	Comfort	395,00
depending on the version	Premium	590,00

Distance Backset Forend (brushed stainless steel)
Standard rounded

German Standard PZ

		20x235x3	24x235x3	20x280x3	24x280x3
72	55	X	X		
72	60	X	X		
72	65	X	X		
72	80	X	X		
92	65			X	X
92	80			X	X

Austrian Standard PZ

		18x250x3	20x250x3	20x300x3
88	50	X	X	X
88	55	X	X	X
88	60	X	X	X
88	65	X	X	X
88	70	X	X	X

Swiss Standard RZ

		20x235x3	24x235x3	18x230x3	20x230x3
74	65	X	X		
78	60			X	X
78	70			X	X
78	80			X	X

i 100 app users
including up to 3 master users



ÜLOCK BL BATTERY SAMPLE STAND

- Sample stand in wood/anthracite look
- Includes high-quality stainless steel door fitting

ART.-N°	DESCRIPTION	€/PIECE
77.96.0090	Sample stand ÜLock BL Battery	580,00



ÜLOCK FULL-LEAF BL INDUCTIVE Comfort or Premium

General product features of ÜLock-B and ÜLock-Z:

- › Self-locking function with 20 mm whisper latch bolt (stainless steel)
- › Inductive power transfer – no battery replacement and no door leaf wiring required
- › Status can be viewed in the app (locked / unlocked)
- › OTA updates directly via the app
- › Office mode (permanently unlocked), either as a one-time setting or on a recurring schedule (adjustable from-to)

Specifications of ÜLock-B:

- › External lever handle can be engaged electrically
- › Premium version incl. certifications:
EN 179 / EN 1125 / EN 1634-1

Specifications of ÜLock-Z:

- › Both lever handles can be engaged electrically
- › No panic function
- › Premium version incl. certifications:
EN 1634-1

Version Z
on request!

ART.-N°	DESCRIPTION	€/PIECE
depending on the version	Comfort	395,00
depending on the version	Premium	590,00

i without striking plate

(suitable striking plates can be found in the main locking systems catalogue)

Distance	Backset	Forend (brushed stainless steel) Standard			
German Standard PZ					
		20x235x3	24x235x3	20x280x3	24x280x3
72	55	X	X		
72	60	X	X		
72	65	X	X		
72	80	X	X		
92	65			X	X
92	80			X	X
Austrian Standard PZ					
		18x250x3	20x250x3	20x300x3	
88	50	X	X	X	
88	55	X	X	X	
88	60	X	X	X	
88	65	X	X	X	
88	70	X	X	X	
Swiss Standard RZ					
		20x235x3	24x235x3	18x230x3	20x230x3
74	65	X	X		
78	60			X	X
78	70			X	X
78	80			X	X

i 100 app users
including up to 3 master users

Find the main
locking systems
catalogue here



ÜLOCK GLASS DOOR LOCK BL BATTERY Comfort

General product features:

- › Backset spacing: 72 mm
- › Backset: 55 mm
- › Self-locking function with 20 mm whisper latch bolt (stainless steel)
- › Electronics protected inside the lock case
- › Tamper-protected, with the programming button integrated into the battery compartment
- › Standard long-life batteries (AAA Energizer Ultimate Lithium)
- › Compatible with Vario Star Top Speed and Flat fittings from Südmetall
- › Round cylinder version available on request
- › Status can be viewed in the app (locked / unlocked)
- › OTA updates directly via the app
- › Office mode (permanently unlocked), either as a one-time setting or on a recurring schedule (adjustable from-to)

Specifications of ÜLock-B:

- › External lever handle can be engaged electrically
- › Panic function

Specifications of ÜLock-Z:

- › Both lever handles can be engaged electrically
- › No panic function

Version Z
on request!

ART.-N°	DESCRIPTION	€/PIECE
77.30.1101	left-hand outward opening	620,00
77.30.1102	right-hand outward opening	620,00
77.30.1103	left-hand inward opening	620,00
77.30.1104	right-hand inward opening	620,00



20 app users
including up to 3 master users

ÜSMART RELAY

A relay with almost unlimited possibilities!

- Fully controllable via the ÜControl app
- 2 outputs with individually assignable functions
- 3 different opening modes (time-based, e.g. 3 seconds; toggle open/close; and on press = active for as long as the button is pressed)
- Can also be paired with the Wi-Fi Hub
- Suitable for applications such as intercom systems, garage doors, swing gates, and in combination with motor locks, electric strikes, and much more
- 12–24 V AC/DC
- Dimensions:
Width A 43 mm x length 75 mm x depth 22 mm
Width B 54 mm x length 75 mm x depth 22 mm

ART.-N°	€/PIECE
77.96.0280	98,00



ÜCONTROL WLAN HUB

Open your doors from anywhere in the world!

- Connection via the home Wi-Fi network
- Battery and lock status of ÜControl hardware products can be accessed
- Communication via Bluetooth and 434 MHz radio
- Up to 2 master users per hub
- Easy management via the ÜControl app
- Multiple products can be used with one hub
- Dimensions: 62 mm x 82 mm x 15 mm

ART.-N°	€/PIECE
77.96.0055 (white)	98,00

ÜCONTROL ACCESS CONTROL



SMARTPHONE

- One-time codes can also be generated remotely without an internet connection. These codes can then be shared with anyone who wants to open the respective door using the ÜControl app installed on their phone
- Fast and stable connection
- All lock settings can be adjusted
- Usage logs can be accessed
- Updates for all devices can be carried out directly via the app



NEW

Available from October 2026



ÜROUND

- Access options: RFID media, smartphone via the ÜControl app
- Can also be operated with all ÜControl access devices such as keypad, fingerprint scanner, facial recognition, etc.
- IP66
- Includes battery replacement tool and 2 x CR2 lithium batteries
- OTA updates directly via the app
- Office mode (permanently unlocked), either as a one-time setting or on a recurring schedule (adjustable from-to)
- Modular configuration for trade customers available on request, eliminating the need for on-site measuring
- Up to 100 RFID identification media can be programmed
- Dimensions:

Electronics side: Ø44 mm, knob length 51 mm

Mechanical side: Ø34 mm, knob length 30 mm

ART.-N°	PROFILE CYLINDER DIMENSIONS	VERSION	€/PIECE
77.951.3232	ÜRound electric cylinder, profile cylinder A32,5/I32,5	ÜControl, stainless steel look	290,00
77.951.3535	ÜRound electric cylinder, profile cylinder A35/I35	ÜControl, stainless steel look	290,00
77.951.3235	ÜRound electric cylinder, profile cylinder A32,5/I35	ÜControl, stainless steel look	290,00
77.951.3532	ÜRound electric cylinder, profile cylinder A35/I32,5	ÜControl, stainless steel look	290,00
77.951.3210	ÜRound electric cylinder, profile cylinder A32,5/I10	ÜControl, stainless steel look, half cylinder	290,00
77.951.3510	ÜRound electric cylinder, profile cylinder A35/I10	ÜControl, stainless steel look, half cylinder	290,00
XXXX	All other sizes up to a total length of 140 mm		324,00

Part number key:

77951 = ÜRound
 77951XX = the first two digits refer to side A (electronics side)
 77951-XX = the second two digits refer to side I (mechanical side)

Example: ÜRound PZ A55-I40 - 779515540



40 app users
including up to 3 master users



ÜCONTROL KEYPAD

- Stores up to 6 passwords
- Power supply: 2 x AA alkaline batteries
- Highly secure wireless communication
- LED graphic display and touch display
- Battery life of at least 1 year
- Dimensions: 55 mm x 60 mm

ART.-N°	DESCRIPTION	€/PIECE
77.96.0240	Keypad IP54	98,00



ÜCONTROL FINGERPRINT READER WITH KEYPAD

- Stores up to 100 fingerprints and up to 6 passwords
- Power supply: 2 x AA alkaline batteries
- Highly secure wireless communication
- LED graphic display and touch display
- Battery life of at least 1 year
- Dimensions: 70 mm x 100 mm x 20 mm

ART.-N°	DESCRIPTION	€/PIECE
77.96.0250	Fingerprint reader with keypad	208,00



ÜCONTROL FACIAL RECOGNITION WITH KEYPAD

- Stores up to 10 passwords and 100 faces
- Power supply: 4 x AA alkaline batteries
- Highly secure wireless communication
- Dimensions: 75 mm x 115 mm x 20 mm

ART.-N°	DESCRIPTION	€/PIECE
77.96.0270	Facial recognition with keypad	250,00



ÜCONTROL REMOTE CONTROL

- Encrypted rolling code
- LED activation indicator
- Long battery life
- Power supply: CR2032 lithium battery
- Dimensions: 35 mm x 58 mm x 12 mm

ART.-N°	DESCRIPTION	€/PIECE
77.96.0210	Remote control	30,00

ÜCONTROL AUTO LOCKING MODULE

- Self-locking module for ÜTopic that automatically locks the door 5 seconds after closing
- Provides a significantly higher level of security
- Consists of a magnet and a self-locking module:
 - The magnet is mounted on the door leaf
 - The auto-locking module is mounted on the door frame
- As soon as the door is closed, the auto-locking module sends a radio signal to the ÜTopic after 5 seconds, instructing it to lock the door
- Easy pairing via the app
- Available in white and black
- Dimensions:
 - 24 mm x 64 mm x 22 mm (self-locking module)
 - 14 mm x 45 mm x 14 mm (magnet)



ART.-N°	DESCRIPTION	€/PIECE
77.96.0230	White	46,00
77.96.0260	Black	55,00



ÜCONTROL SMART HOME AUTOMATION INTERFACE

- For on-site Bluetooth control of ÜControl hardware
- 5–12 V DC
- Current consumption: up to 30 mA
- Temperature range: 0–40°C
- Wireless range: up to 5 metres, depending on environmental conditions
- Function commands: normal, toggle and delay
- Easy pairing via the app
- Dimensions: 30 mm x 50 mm x 14 mm

ART.-N°	DESCRIPTION	€/PIECE
77.96.0220	Smart Home Interface	64,00

BEDIENUNGSANLEITUNG ÜCONTROL VIDEO



OPERATING INSTRUCTIONS



INSTRUCTIONAL VIDEO

Südmetall®

Sales & Logistics: Süd-Metall Beschläge GmbH

Sägewerkstrasse 5 | 83404 Ainring / Hammerau | T +49 (0) 8654 4675 50 | F +49 (0) 8654 4675 70

Email: info@suedmetall.com | www.suedmetall.com

Development & Production: Süd-Metall Schließsysteme Leipzig GmbH

Apelsteinallee 1 | 04416 Markkleeberg | www.suedmetall-schliesssysteme.com

Find us on     

All information is subject to colour deviations and printing errors due to printing technology.

The general terms of delivery and payment per to our website apply. The general terms and conditions of Süd-Metall Beschläge GmbH apply.

We reserve the right to make technical changes to our products. The publication of this price list voids all previous price lists and price agreements. This price list is intended exclusively for the B2B (business customer sector). This price list is not intended to be passed on to end customers, as the prices are all exclusive of the respective statutory value added tax. All prices per piece (unless otherwise stated), GROSS in € (euro).

Prices valid until a new price list is published and only while stocks last.

We, SÜD-METALL BESCHLÄGE GMBH, Sägewerkstraße 5, D - 83404 Ainring / Hammerau, are the responsible party in terms of data protection law.

If you are not yet our customer or have voluntarily provided us with your data for the purpose of contacting us, your data originates from our own research via freely accessible resources such as yellow pages, networking platforms, trade registers and similar. The processing of your data for the purpose of marketing is carried out without your consent in accordance with Art. 6 Para. 1 (1) lit f) of the GDPR for information in line with your interests. In any case you can object to us processing for marketing purposes for the future at any time. For more information on your other rights, e.g. to information, correction, deletion, your rights of appeal and the data protection officer, please refer to our data protection declaration, available at <https://www.suedmetall.com/4/datenschutz/> and our data protection information sheet, available at https://www.suedmetall.com/fileadmin/user_upload/downloads/Information_Datenschutz_D-EN.pdf.



Art.-Nr. 36.06.7602